

APCO Waterborne Primer Sealer

Production Description

APCO Waterborne Primer Sealer is a specially formulated rapid dry waterborne multi-functional product for use along with APCO Fast Dry Waterborne Paint to achieve best performance. It can be applied directly onto surfaces and provide adhesion promotion for APCO Fast Dry Waterborne Paint where the paint may experience difficulty in maintaining adhesion. It can also be used to seal APCO Fast Dry Waterborne Paint to improve dust and dirt resistance of the marking in situations where the coating is not exposed to cleaning actions of the weather.

Areas of Application

Use APCO Waterborne Primer Sealer to pre-treat all concrete surfaces on concrete masonry surfaces before application of APCO Waterborne Primer Sealer.

Use APCO Waterborne Primer Sealer to seal APCO Fast Dry Waterborne marking in dusty environments

Technical Data

Composition	Emulsified Pure Acrylic Polymer
Specific Gravity	1-1.02
Appearance	Milky White Liquid, Dries Clear
Thinner	Not Required. Supplied RFU (Ready for Use) Do not thin
Cleaning Solvent	Water
Volume Solids	Approx. 35%
Coverage	8 – 12 sq metres per litre depending on surface profile
Packs available	20 litres
Drying Time (at 25°C & RH 60%)*	Less than 3 minutes

*Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Application

APCO Waterborne Primer Sealer can be applied by spray, rolled or brushed directly to the road or marking surface. Always allow APCO Waterborne Primer Sealer to dry before over coating with APCO Fast Dry Waterborne Paint, which takes a few minutes. When used as sealer allow to dry before exposing to traffic. Longer period will give better performance.

Surface Preparation

Ensure that the area where line marking is to be done is clean and free from all dirt, dust, grease, oil, loosely adhered material and all other surface contamination. If any mould or fungus is present on the surface, wash it with a commercial bleaching agent and then with rinse with clean water. Allow the surface to dry fully before application.

Flammability & Transport

- Non-flammable.
- Not classified as dangerous goods by ADG Code
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Environmental

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.
- Refer to state / local EPA and council web sites for environmental and safe disposal details.

APCO Waterborne Primer Sealer

Safety & Precautions

- Do not apply when surface temperature is below 10⁰ C.
- Do not apply in environments of high humidity/moisture, or if pending rain is a possibility.
- Apply in calm fine weather conditions.
- Provide adequate ventilation during use.
- Keep out of reach of children
- Apply a test sample for compatibility of this product over a small test area.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

APCO Coatings (Sydney) 111 Kurrajong Avenue Mt Druitt NSW 2770 Phone (02) 9832 0000

APCO Coatings (Brisbane) 444 Newman Road Geebung QLD 4051 Phone (07) 3265 7890

E-mail: sales@apccoatings.com.au

Website: www.apccoatings.com.au

Reviewed Dec 2014