

PoolKote Epoxy Pool Paint – Part B

SECTION 1- IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: PoolKote Epoxy Pool Paint – Part B
 Manufacturing Product Code: Z4419
 Recommended Uses: Hardener for epoxy concrete or fiber glass pool coating
 Supplier: Asian Paints (Queensland) Pty Ltd
 Street Address: 111, Kurrajong Ave, Mount Druitt, NSW, 2770
 Telephone Number: (02) 9832 0000
 Fax: (02) 9677 0566
 Emergency phone: **Poison Information Center: 13 11 26**

SECTION 2- HAZARDS IDENTIFICATION

Health Hazard Classification

This product is classified as hazardous under SafeWork Australia criteria.

Hazard Category

F: Flammable; Xn: Harmful; Xi: Irritant

Risk Phrases

R10: Flammable
 R20/21/22: Harmful by inhalation, in contact with skin and swallowed.
 R37/38: Irritating to skin and respiratory system
 R41: Risk of serious damage to eyes.
 R67: Vapors may cause drowsiness and dizziness

Safety Phrases

S2: Keep out of reach of children.
 S 7/9: Keep container tightly closed and in a well-ventilated place.
 S13: Keep away from food, drink and animal feeding stuffs.
 S25: Avoid contact with eyes
 S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S37/39: Wear suitable gloves and eye/face protection.
 S46: If swallowed, seek medical advice immediately and show this container or label.

SECTION 3- COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Entity	CAS No.	Proportion (%w/w)
Xylene	1330-20-7	30-60%
Butanol	71-36-3	<10%
Ingredients determined to be non-hazardous or below the hazardous threshold		TO 100%

SECTION 4- FIRST AID MEASURES**Ingestion**

If swallowed, do not induce vomiting. Give 250 ml water to rinse out mouth and drink. Seek immediate medical attention.

Eye contact

Immediately flush eyes with large amount of water for at least 15 minutes. Seek immediate medical attention.

Skin contact

Remove contaminated clothing. Immediately flush skin with large amount of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Inhalation

Remove victim from exposure to fresh air. Keep at rest. If breathing is difficult, administer artificial respiration. Seek immediate medical attention

First aid facilities

Provide eye baths and safety showers.

Medical attention

Treat symptomatically.

SECTION 5- FIRE FIGHTING MEASURES**Suitable extinguishing equipment**

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.

Hazards arising from combustion of product

Oxides of Carbon.

Special protective equipment and precautions for fire fighters

Wear breathing apparatus when fighting fire.

Hazchem Code: 3[Y]E

SECTION 6- ACCIDENTAL RELEASE MEASURES**Minor spill**

Extinguish naked flames. And avoid sparks. Absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations.

Major spill

Extinguish naked flames and avoid sparks. Wear appropriate protective clothing and equipment. Evacuate surrounding personal. Dike area of spill, and transfer to empty drums. Residue to be absorbed with sand, sawdust or earth, and placed in drums. Arrange disposal by competent contractor, in accordance with local regulations.

SECTION 7- HANDLING AND STORAGE**Precaution for safe handling**

This product is flammable. Avoid sources of heat, naked flames and sparks. Use in well-ventilated area. Use flame proof equipment. No smoking. Earth all containers to reduce the possibility of sparks from static electricity.

Conditions for safe storage

Store in a cool, well-ventilated area and place away from heat, naked flames and sparks. Store away from oxidizing agents, alkaline materials and strong acids. Keep container closed at all times. Keep away from food, and drink and clothing.

SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Entity	Cas No	Weight%	TWA ¹ (ppm)	STEL ² (ppm)
Xylene	1330-20-7	30-60%	100	150
Butanol	71-36-3	<10%	100	N/A

¹ Time weighted average concentration

² Short-term exposure limit

Engineering controls

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TWA. Ventilation equipment should be explosion proof.

Personal protective equipment

Wear chemical safety glasses/goggles or face shield. Wear half face respirator, with organic vapor cartridge. Wear PVC or Nitrile chemical handling gloves.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Brownish Liquid
Odour	-	Amine Odour
Boiling Point	°C	127
Flash Point	°C	31
Density @ 25°C	g/ml	1.55-1.65
Flammability Limits	%(v/v)	1-7
Volatile content	%(w/w)	>60
Solubility in water	-	Limited

SECTION 10- STABILITY AND REACTIVITY**Chemical stability**

Stable at room temperature and pressure.

Conditions to avoid

Source of heat and ignition, open flames.

Incompatible materials

Strong oxidizing agents, Alkali and Alkaline Metals, Halogens, Mineral acids.

Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

Hazardous polymerization

Will not occur.

SECTION 11- TOXICOLOGICAL INFORMATION**Acute effects*****Ingestion***

Slightly toxic. Main hazard of ingestion is aspiration of swallowed liquid into lungs, causing chemical pneumonitis.

Eye Contact

Irritating, causing redness and burning sensation.

Skin Contact

Irritating, causing redness and burning sensation.

Inhalation

Harmful by inhalation. The vapour is irritating to the upper respiratory tract. May cause nausea, dizziness and narcosis. Extreme exposure may result in unconsciousness, and possibly death.

Chronic effects

Prolonged and repeated contact with the skin may irritate, and cause dermatitis. Prolonged overexposure to the solvents (inhalation and skin contact) may cause effects to the central nervous system, liver, urinary, blood forming, cardiovascular and reproductive systems.

Toxicology information

Chemical Entity	Weight %	Oral LD ₅₀ (Rat) mg/kg	Dermal LD ₅₀ (Rat or rabbit) mg/kg	LC ₅₀ Inhalation (Rat) mgL ⁻¹ /4 hr

Xylene	10-30%	>2000	>2000	>20
Butanol	1-10%	>790	>3400	N/A

SECTION 12- ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SECTION 13- DISPOSAL CONSIDERATIONS

Do not let this product enter the environment. Dispose of this material and its container as hazardous waste. Do not pour unwanted paint or paint-related material down the drain. Keep unwanted material in sealed containers for disposal via special chemical waste collections. Empty paint containers should be left open in a well-ventilated area to dry out. When dry recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities check with your local council first.

SECTION 14- TRANSPORT INFORMATION

For local transportation within New Zealand refer NZS 5433:1999: For Australia refers ADG code.

UN No.	1263
Proper Shipping Name	Paint
DG Class	3
Subsidiary Risk	Not Applicable
Packing Group	III
Hazchem Code	3[Y] E

SECTION 15-REGULATORY INFORMATION

HMIS Code: 230H

SECTION 16- OTHER INFORMATION

Contact Apco Coatings
Person/Point Technical Manager
 Ph 02 98 32 0000 Mob 0422237710

Other Information Principal toxic properties of this product are due to the solvent composition and vapour inhalation hazards.

Abbreviations: N/A - Not Applicable N/AV - Not Available

Abbreviations:

ADG: Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number: Chemical Abstracts Number