

Chlorinated Rubber Thinner

Production Description

Chlorinated Rubber Thinner is a aromatic hydrocarbon based solvent with moderate evaporation rate. It provides relatively fast initial flash off allowing for better vertical holdup.

Areas of Application

Can be used as thinner for Chlorinated Rubber based solvent based paints and other solvent based paints as specified in the relevant product.

Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.87
Boiling Range	135 - 155 °C
Thinning Recommendations	Spray application : 10-15% as required Brush/Roller application: up to 10% as required. Application to concrete (first coat only): 20-25% to assist penetration into surface.
Packs available	1 litre, 4 litre & 20 litre

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Safety & Precautions

Refer to SDS for detail instructions.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 111 Kurrajong Avenue Mt Druitt NSW 2770 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed Sep 2017