



Australian Made & Australian Owned



# Epoxy Thinner

**Production Description**  
Blended thinner for reducing Two Pack Epoxy coatings to a suitable spraying viscosity. It allows epoxy greater penetration into surfaces when added to a first coat. Epoxy thinner provides fast initial flash off allowing for better vertical hold up.

**Areas of Application**  
Can be used as thinner for Two Pack Epoxy products.

Technical Data	
Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.85
Boiling Range	80-143 °C
Thinning Recommendations	Spray application: 10-15% as required Brush/Roller application: up to 10% as required. Application to concrete (first coat only): 20-25% to assist penetration into surface.
Packs available	1 litre, 4 litre & 20 litres

- Flammability & Transport**
- Highly flammable, Dangerous Goods Class 3.2.
  - Keep away from heat and flame, eliminate any source of ignition.
  - Soak all used cloths and rags immediately in water to prevent self-ignition.
  - Ensure container is upright with lid secure.
  - Ensure the container is secured in the vehicle for transport.

**Safety & Precautions**  
Refer to SDS for detail instructions.

Disclaimer: In lieu of all warranties expressed or implied, the seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable for any injury, loss, damage, direct or consequential, arising out of the use of or inability to use this product. Since the use and application of this product is beyond the control of the seller and the manufacturer, the purchaser and user assume all risk and liability whatsoever, in connection with this product therewith.

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2765 Phone (02) 9832 0000 /  
info@omegapaints.com.au  
Reviewed April 2021