

Omega 199 Two Pack Epoxy Primer -Part B

SECTION 1- IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Omega 199 Two Pack Epoxy Primer -Part B
Manufacturing Product Code: Z48460
Recommended Uses: For priming metal
Supplier: Omega International Coatings P/L
Street Address: 111, Kurrajong Ave, Mount Druitt, NSW, 2770
Telephone Number: (02) 9832 0000
Fax: (02) 9677 0566
Emergency phone: **Poison Information Center: 13 11 26**

SECTION 2- HAZARDS IDENTIFICATION

Health Hazard Classification

This product is classified as hazardous under SafeWork Australia criteria.

Hazard Category

F: Flammable; Xn: Harmful; Xi: Irritant;

Risk Phrases

R11: Highly flammable.
R20/21: Harmful by inhalation and in contact with skin.
R36/37/38: Irritating to eyes, respiratory system and skin.
R66: Repeated exposure may cause skin dryness or cracking.

Safety Phrases

S2: Keep out of the reach of children.
S9: Keep container in a well-ventilated place.
S16: Keep away from sources of ignition - No smoking.
S25: Avoid contact with eyes.
S29: Do not empty into drains.

SECTION 3- COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Entity	CAS No.	Proportion (%w/w)
Methyl isobutyl ketone	108-10-1	10-30%
Xylene	1330-20-7	10-30 %
Ingredients determined to be non-hazardous Or below the hazardous threshold		TO 100%

SECTION 4- FIRST AID MEASURES**Ingestion**

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Eye contact

Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.

Skin contact

Remove contaminated clothing. Immediately flush skin with large amount of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Inhalation

Remove victim from exposure to fresh air. Keep at rest and seek medical attention immediately. If breathing is difficult, administer oxygen or artificial respiration. Seek immediate medical attention.

First aid facilities

Provide eye baths and safety showers.

Medical attention

Treat symptomatically.

SECTION 5- FIRE FIGHTING MEASURES**Suitable extinguishing equipment**

Dry powder, Alcohol-resistant foam. Carbon dioxide, sand or earth may be used for small fires only.

Hazards arising from combustion of product

Oxides of Carbon, isocyanate vapors and other irritating highly toxic gases.

Special protective equipment and precautions for fire fighters

Wear self-contained breathing apparatus and protective suit.

Hazchem Code: 3[Y]E

SECTION 6- ACCIDENTAL RELEASE MEASURES**Minor spill**

Extinguish naked flames. And avoid sparks. Absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations.

Major spill

Extinguish naked flames and avoid sparks. Wear appropriate protective clothing and equipment. Evacuate surrounding personal. Dike area of spill, and transfer to empty drums. Residue to be absorbed with sand, sawdust or earth, and placed in drums. Arrange disposal by competent contractor, in accordance with local regulations.

SECTION 7- HANDLING AND STORAGE**Precaution for safe handling**

This product is highly flammable. Avoid sources of heat, naked flames and sparks. Avoid contact with skin, eyes, and clothing. Use in well-ventilated area. Do not breathe vapors, mists, or dusts. Use flame proof equipment. No smoking. Earth all containers to reduce the possibility of sparks from static electricity.

Conditions for safe storage

Store in a cool, well-ventilated area and place away from heat, sunlight, naked flames and sparks. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Keep container closed at all times. Keep away from food, and drink and clothing.

SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Entity	Cas No	Weight%	TWA ¹ (ppm)	STEL ² (ppm)
Methyl isobutyl ketone	108-10-1	<10%	20	50
Xylene	1330-20-7	30-60 %	100	150

¹ Time weighted average concentration

² Short-term exposure limit

Engineering controls

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below TWA. Ventilation equipment should be explosion proof.

Personal protective equipment

Wear chemical safety glasses/goggles or face shield. Wear half face respirator, with organic vapor cartridge. Wear PVC or Nitrile chemical handling gloves.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Clear to yellow liquid
Odour	-	Solvent Odour
Vapor Pressure @ 25°C	kPa	0.01
Boiling Point	°C	130
Flash Point	°C	26
Density @ 25°C	g/ml	0.96 - 1.00
Flammability Limits	%(v/v)	N/A
Volatile content	%(w/w)	>40

SECTION 10- STABILITY AND REACTIVITY**Chemical stability**

Stable at room temperature and pressure.

Conditions to avoid

Source of heat and ignition, open flames and sparks

Incompatible materials

Water, amines, strong bases, alcohols, copper alloys

Hazardous decomposition products

Carbon oxides, oxides of nitrogen, and other organic complexes on incomplete burning or oxidation.

Hazardous reactions

Oxidizing agents, mineral acids, halogenated organic compounds and peroxides.

SECTION 11- TOXICOLOGICAL INFORMATION**Acute effects*****Ingestion***

Slightly toxic. Main hazard of ingestion is aspiration of swallowed liquid into lungs, causing chemical pneumonitis.

Eye Contact

Irritating, causing redness and burning sensation.

Skin Contact

Irritating, causing redness and burning sensation.

Inhalation

Harmful by inhalation. The vapour is irritating to the upper respiratory tract. Cause nausea, dizziness and narcosis. Extreme exposure will result in unconsciousness, and possibly death.

Chronic effects

Prolonged and repeated contact with the skin may irritate, and cause dermatitis. Prolonged overexposure to the solvents (inhalation and skin contact) may cause effects to the central nervous system, liver, urinary, blood forming, cardiovascular and reproductive systems.

Toxicology information

No LD data available for this product.

SECTION 12- ECOLOGICAL INFORMATION

Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SECTION 13- DISPOSAL CONSIDERATIONS

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Advise flammable nature. Product is normally suitable for incineration by an approved agent.

SECTION 14- TRANSPORT INFORMATION

For local transportation within New Zealand refer NZS 5433:1999: For Australia refers ADG code.

UN No.	1263
Proper Shipping Name	Paint
DG Class	3
Subsidiary Risk	Not Applicable
Packing Group	III
Hazchem Code	3[Y] E

SECTION 15-REGULATORY INFORMATION

HMIS Code: 230H

SECTION 16- OTHER INFORMATION

Contact Apco Coatings
Person/Point Technical Manager
Ph 02 98 32 0000 Mob 0422237710

Other Information Principal toxic properties of this product are due to the solvent composition and vapour inhalation hazards.

Abbreviations: N/A - Not Applicable N/AV - Not Available

Abbreviations:

ADG: Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number: Chemical Abstracts Number