

2 Pack Epoxy Thinners

Production Description

Blended thinner for reducing 2 Pack Epoxy coatings to a suitable spraying viscosity. It allows epoxy greater penetration into surfaces when added to a first coat. 2 Pack Epoxy thinner provides fast initial flash off allowing for better vertical hold up.

Areas of Application

Can be used as a thinner for 2 Pack Epoxy Thinners products.

Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.85-0.86
Boiling Point	80-110 °C
Packs available	4 litre 20 litre, 60 litre & 200 litre

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Environmental

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.
- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Safety & Precautions

- Provide adequate ventilation during use.
- Keep out of reach of children
- Apply a test sample for compatibility of this product over a small test area.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd

111 Kurrajong Avenue, Mount Druitt NSW 2770

t. (02) 9832 5900 | f. (02) 9677 0566

www.omegapaints.com.au

Date of Revision: August 2016