

## M.E.K. Thinner

### Production Description

Methyl Ethyl Ketone (M.E.K.) is a solvent with strong sharp odour. It has great solvency and is recommended as a thinner for system involving nitrocellulose, cellulose acetate, vinyl film and many rubbers. Also it can be used as a high quality gun wash.

### Areas of Application

Recommended to be used as thinner or clean-up solvent for 2 pack polyurethane and 2 pack epoxy.

### Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.80
Boiling Range	79-80 °C
Thinning Recommendations	Generally 5-10% is required. Refer individual product data sheet for specific recommendations.
Packs available	4 litre, 20 litre & 60 litre

### Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

### Safety & Precautions

Refer to SDS for detail instructions.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 111 Kurrajong Avenue Mt Druitt NSW 2770 Phone (02) 9832 0000 /  
info@omegapaints.com.au  
Reviewed Sep 2017