



PREMIUM PAINT

Australian Made & Australian Owned



# Wax & Grease Remover

## Production Description

Wax & Grease Remover is a highly effective blend of solvent which effectively removes wax, grease, polish, oil, tar, grime, glue and most other contaminants prior to sanding and finishing.

## Areas of Application

Recommended for use as re-painting surface cleaner, heavy duty cleaning solvent. Suitable for use for removing wax, gum/ sticker residual from windows, carpet, furniture and timber surfaces.

## Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.80
Boiling Range	95-100 °C
Thinning Recommendations	Apply liberal amount to surface being cleaned. Always use clean HT11 wax & grease remover and clean rags. Always remove by wiping in one direction only
Packs available	4 litre, 20 litre & 60 litre

## Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

## Safety & Precautions

Refer to SDS for detail instructions.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone NSW 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed Nov 2018