



Wax & Grease Remover

Production Description

Wax & Grease Remover is a highly effective blend of solvent which effectively removes wax, grease, polish, oil, tar, grime, glue and most other contaminants prior to sanding and finishing.

Areas of Application

Recommended for use as re-painting surface cleaner, heavy duty cleaning solvent. Suitable for use for removing wax, gum/ sticker residual from windows, carpet, furniture, and timber surfaces.

Technical Data	
Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.80
Boiling Range	99-199 °C
Thinning Recommendations	Apply liberal amount to surface being cleaned. Always use clean HT11 wax & grease remover and clean rags. Always remove by wiping in one direction only
Packs available	4 litre, 20 litre & 60 litre

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Safety & Precautions

Refer to SDS for detail instructions.

Disclaimer: In lieu of all warranties expressed or implied, the seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable for any injury, loss, damage, direct or consequential, arising out of the use of or inability to use this product. Since the use and application of this product is beyond the control of the seller and the manufacturer, the purchaser and user assume all risk and liability whatsoever, in connection with this product therewith.

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2765 Phone (02) 9832 0000 / info@omegapaints.com.au Reviewed April 2021