



Australian Made & Australian Owned



M.E.K. Thinner

Production Description

Methyl Ethyl Ketone (M.E.K.) is a solvent with strong sharp odour. It has great solvency and is recommended as a thinner for system involving nitrocellulose, cellulose acetate, vinyl film and many rubbers. Also, it can be used as a high-quality gun wash.

Areas of Application

Recommended to be used as thinner or clean-up solvent for 2 pack polyurethane and 2 pack epoxy.

Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.80
Boiling Range	79-80 °C
Thinning Recommendations	Generally, 5-10% is required. Refer individual product data sheet for specific recommendations.
Packs available	4 litre, 20 litre & 60 litre

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Safety & Precautions

Refer to SDS for detail instructions.

Disclaimer: In lieu of all warranties expressed or implied, the seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable for any injury, loss, damage, direct or consequential, arising out of the use of or inability to use this product. Since the use and application of this product is beyond the control of the seller and the manufacturer, the purchaser and user assume all risk and liability whatsoever, in connection with this product therewith.

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2765 Phone (02) 9832 0000 /
info@omegapaints.com.au
Reviewed April 2021