



Australian Made & Australian Owned



# Xylene

## Production Description

Xylene is a medium evaporating solvent with great solvency. It is recommended as a thinner for spraying application where fast curing is desired.

## Areas of Application

Can be used as thinner for spray applications. It has good solvency for dissolving various resin systems.

## Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.86
Boiling Point	140 °C
Thinning Recommendations	Spray application: 5 to 10% is required, depending on product. Refer individual product data sheet for specific recommendations.
Packs available	1 litre, 4 litre, 20 litre, 60 litre & 200 litre

## Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

## Safety & Precautions

Refer to SDS for detail instructions.

Disclaimer: In lieu of all warranties expressed or implied, the seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable for any injury, loss, damage, direct or consequential, arising out of the use of or inability to use this product. Since the use and application of this product is beyond the control of the seller and the manufacturer, the purchaser and user assume all risk and liability whatsoever, in connection with this product therewith.

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed April 2021