



Australian Made & Australian Owned



## Chlorinated Rubber Thinner

### Production Description

Chlorinated Rubber Thinner is a aromatic hydrocarbon based solvent with moderate evaporation rate. It provides relatively fast initial flash off allowing for better vertical holdup.

### Areas of Application

Can be used as thinner for Chlorinated Rubber based solvent based paints and other solvent based paints as specified in the relevant product.

### Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.87
Boiling Range	135 - 155 °C
Thinning Recommendations	Spray application: 10-15% as required Brush/Roller application: up to 10% as required. Application to concrete (first coat only): 20-25% to assist penetration into surface.
Packs available	1 litre, 4 litre & 20 litre

### Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

### Safety & Precautions

Refer to SDS for detail instructions.

Disclaimer: In lieu of all warranties expressed or implied, the seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable for any injury, loss, damage, direct or consequential, arising out of the use of or inability to use this product. Since the use and application of this product is beyond the control of the seller and the manufacturer, the purchaser and user assume all risk and liability whatsoever, in connection with this product therewith.

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed April 2021